



Manufacture, Installation & Servicing of all type of Elevators

Profile

E

CRYSTAL ELEVATORS is one of the South India's leading elevator company. As a step up in vertical integration based on the concerns of QUALITY, COST, TIMELY EXECUTION and DEPENDABLE SERVICE with a well experienced Engineers team. CRYSTAL ELEVATORS is a unique brand having the well experienced technical team having various multi national companies.

Our goal is to realize elevator with advanced technology of equipment, erection and commissioning with strong technical knowledge, good after service, supplying high quality products under strict quality control system. Following Bureau of Indian Standards (BIS) guide lines and guarantee excellent result in terms of safety performance and reliability.

The company owns the customers trust and praise. CRYSTAL ELEVATORS is ready to face the challenges of transporting people and vehicles within modern metropolitan buildings, with a complete equipment and flexible customization capabilities that today represents an international benchmark for quality.


Our services are available to the customers on 24x7 basis. Call back numbers, 2 wheelers and mobile phones are used for punctual and reliable services. We are competent to service all types of make elevators with a reasonable pricing.



Cabins / Car



We believe that the appearance of an elevator's interior can improve the morale of the passengers that it is carrying. We can design and install new elevator cabins and ceilings using stainless steel and powder coated mild steel that suits your building aesthetics.



Elevator Doors



Control Panels



• 16 bit micro-controller based single board design.

- Pure Sine Wave output fully digital settings.
- Trimpot less LCD gives complete insight of the various parameters, user friendly messages on the display.
- Door Operator Any power operated doorsormanual entrances.

Powered by 16 bit micro controller providing complex functionality.

- Wall mounted compact, space saving design.
- Position & Direction indicator in control paneltomonitorcarmovement.
- Fireman operation with programmable floorelectrically isolated power supply.



Our elevator controllers, acting as the "brain" of a lift system, are equipped with a microprocessor that is designed to operate in the most effective way.

Thanks to the technique of detachable boards and the flexible programming system.

Machines



- These machines are small, compact, light with great performance.
- All have worm of hardened ground steel.
- The crown is of centrifugally cast antifriction bronze.
- The break is equipped with independent jaws as well as a twin magnetic circuit and is available in various voltage.
- Permanent magnets synchronous motor with Brush-less technology.
- High load capacity.
- Silent & Jerk free ride.
- Comfort Safety.
- Energy Saving.
- Maxium static load up to 200 kg & speed up to 2 m/s



Our Traction Machines are manufactured in strict accordance to its uncompromising quality control methods right from the initial stage of procurement of raw material to the final stage of the testing, inspection and dispatch to customers and in keeping with the latest technology.















E


Integrated Drive



Fuji Drive



MRL ELEVATOR CROSS SECTION



COP and **LOP**

E







- ^o Attractive Front Plate of SS₃₀₄
- Available on different kinds of plate finish i.e. Hairline, Mirror, Anodize etc.
- Available in various kind of attractive push buttons.
- Display varieties like 7-Segment, Dot Matrix LCD, TFT available .
- ^o Emergency Light, Push to Talk(Intercom) can be Incorporated.
- Interfacing of RF ID & Biometric Based access.
- Customized Length & fixing arrangement.











Z





Sheet Designs





GOLD Hairline



TE4



Y3D 05



YTEX01



YTEX05



YTEX10



Hairline

TE06

Y3D 06

YTEX02

YTEX05E

YTEX11







Y3D 01


YCheq 02





TE01

Ycheq1



YTEX03





YTEX13



Y3D 03

YTEX 01(Bronze)

YTEX03E

YTEX08

YTEX14



TE03



Y3D 04



YTEX01 E



YTEX04E



YTEX09



YTEX15



YTEX06





False Ceiling and Handrails



E




























Elevator Types



| | TYPES OF ELEVATOR | | | | | | | | |
|---------|--|---------------------|----------------|--|--|--|--|--|--|
| SI. No. | Specification | Lift Capacity | Speed | | | | | | |
| 1 | Passenger elevators | 4 to 29 persons | 1.0 to 2.5 MPS | | | | | | |
| 2 | Observation elevators(also referred capsule/ scenic/ panoramic) | 6 to 20 persons | 1.0 to 2.5 MPS | | | | | | |
| 3 | Goods or freight elevators | 500 Kgs to 5000 Kgs | Up to 0.75 MPS | | | | | | |
| 4 | Hospital bed or stretcher elevators | 15 to 26 person | Up to 1.5 MPS | | | | | | |
| 5 | Dumbwaiters | 100 Kgs to 250 Kgs | Up to 0.3 MPS | | | | | | |
| 6 | Home elevators | 4 persons | Up to 0.4 MPS | | | | | | |
| 7 | Stair lifts | Customized in KGS | NA | | | | | | |

| TYPES OF MACHINES | | | | | | | | |
|---------------------------------------|------------------------------|--|--|--|--|--|--|--|
| Gearless PMSM (Permanent Magnet | Conventional geared traction | | | | | | | |
| Synchronous Moto) | | | | | | | | |
| MRL (Machine Room Less) gearless PMSM | Hydraulic Machine Unit | | | | | | | |
| TYPES OF OPERATION | | | | | | | | |
| Down Collective/ Full Collective | Simplex/ duplex/ triplex | | | | | | | |

| TYPES | OF | DO | ODC | |
|-------|----|----|-----|--|
| TPES | | | URS | |
| | | | | |

- Canter Opening Automatic VVVF, of 2 panels for passenger elevators and 4 panels for goods elevators.
 Telescopic (side opening) automatic VVVF, 2 and 3 panel options.
- Semi Auto Telescopic Auto in car and Swing Door in landings.
- Manual Imperforated in car, Imperforated or Swing Doors in landings.
 - > Doors in SS with a range of finish options and in MS with standard painting and powder coating options.

KEY SAFETY FEATURES

- ARD (Automatic Rescue Device) using sealed SMF batteries.
- Full height multi-beam (154 beams) infrared door safety.
- Over speed governor.
- Close loop encoder feedback for smooth and jerk free landing with V3F drive.
- > Automatic doors too with V3F drive and close loop encoder feedback, for smooth Door operation
- Overload warning

8

E

| | PASSENGER ELEVATORS | | | | | | | | |
|---------|---------------------|-------|-------|------|-------------------|------|----------------|------|-----------|
| Lo | ad | Car I | nside | Lift | Lift Well Entranc | | e Machine Room | | Door type |
| Persons | Kg | A | В | С | D | E | K | L | L |
| 4 | 272 | 1100 | 700 | 1600 | 1200 | 800 | 3100 | 3600 | Manual |
| 5 | 340 | 1100 | 900 | 1600 | 1400 | 800 | 3100 | 3600 | Manual |
| 6 | 408 | 1100 | 1000 | 1600 | 1500 | 800 | 3100 | 3900 | Manual |
| 8 | 544 | 1300 | 1100 | 1800 | 1600 | 800 | 3300 | 4050 | Manual |
| 4 | 272 | 1100 | 700 | 1600 | 1350 | 700 | 3100 | 3850 | Automatic |
| 5 | 340 | 1100 | 900 | 1600 | 1500 | 700 | 3100 | 4000 | Automatic |
| 6 | 408 | 1100 | 1000 | 1900 | 1600 | 800 | 3400 | 4100 | Automatic |
| 8 | 544 | 1300 | 1100 | 1900 | 1900 | 800 | 3400 | 4400 | Automatic |
| 10 | 680 | 1350 | 1300 | 1900 | 2100 | 800 | 3400 | 4600 | Automatic |
| 13 | 844 | 2000 | 1100 | 2500 | 1900 | 900 | 4000 | 4400 | Automatic |
| 16 | 1088 | 2000 | 1300 | 2500 | 2100 | 1000 | 4000 | 4600 | Automatic |
| 20 | 1360 | 2000 | 1550 | 2500 | 2400 | 1000 | 4000 | 4900 | Automatic |
| 26 | 1768 | 2100 | 1800 | 2600 | 2500 | 1100 | 4200 | 5000 | Automatic |

| | FREIGHT ELEVATORS | | | | | | | |
|-------------|-------------------|-------|------|------|----------|--------|--------|----------|
| Load | Car I | nside | Lift | Well | Entrance | Machin | e Room | M/C Room |
| Load in Kgs | A | В | С | D | E* | K | L | Height |
| 800 | 1550 | 1500 | 2000 | 2000 | 900 | 2500 | 4500 | 2300 |
| 1000 | 1400 | 1800 | 2300 | 2100 | 1400 | 2500 | 4600 | 2300 |
| 1500 | 1700 | 2000 | 2600 | 2300 | 1700 | 2600 | 4800 | 2300 |
| 2000 | 1700 | 2500 | 2600 | 2800 | 1700 | 2600 | 5300 | 2300 |
| 2500 | 2000 | 2500 | 2800 | 2750 | 2000 | 2800 | 4700 | 2300 |
| 3000 | 2000 | 3000 | 2900 | 3300 | 2000 | 2900 | 5800 | 2300 |
| 4000 | 2500 | 3000 | 3400 | 3300 | 2500 | 3400 | 5800 | 2300 |
| 5000 | 2500 | 3600 | 3400 | 3900 | 2500 | 3400 | 6400 | 2300 |

* Clear Entrance width is based on Vertical Lifting Car Door and Vertical Bi-parting doors. For Collapsible Mid Bar Doors, the clear entrance width will be reduced by 200mm (max 1200 mm).

| | HOSPITAL ELEVATORS | | | | | | | | |
|---------|--|------|------|------|------|------|------|------|----------|
| Lo | Load Car Inside Lift Well Entrance Machine Room M/C Room | | | | | | | | M/C Room |
| Persons | Kgs | A | В | С | D | E | K | L | Height |
| 15 | 1020 | 950 | 2400 | 1700 | 3000 | 800 | 3700 | 5500 | 2300 |
| 20 | 1360 | 1300 | 2400 | 2200 | 3000 | 1200 | 4200 | 5500 | 2300 |
| 20 | 1768 | 1600 | 2400 | 2350 | 3000 | 1200 | 4350 | 5500 | 2300 |

| | SERVICE ELEVATORS / DUMB WAITER | | | | | | | | |
|-------------|---------------------------------|------------|------|------------------------------------|------|---------|--------|----------|--------|
| Load | Car speed | Car Inside | | peed Car Inside Lift Well Entrance | | Machine | e Room | M/C Room | |
| Load in kgs | M.PS. | А | В | С | D | E* | K | L | Height |
| 100 | 0.50 | 700 | 700 | 1200 | 900 | 700 | 1200 | 1150 | 2300 |
| 150 | 0.50 | 800 | 800 | 1300 | 1000 | 800 | 1300 | 1150 | 2300 |
| 200 | 0.50 | 900 | 900 | 1400 | 1100 | 900 | 1400 | 1150 | 2300 |
| 250 | 0.70 | 1000 | 1000 | 1500 | 1200 | 1000 | 1500 | 1200 | 2300 |

| Speed (MPS) | Pit Depth | Overhead |
|--------------------|-----------|----------|
| Upto 1.50 | 1600 | 4800 |
| Over 1.50 upto 2.5 | 2600 | 5700 |
| Over 2.5 | 2600 | 6700 |

** All hoistway walls should be minimum 230 Brick or 150 RCC.
* All dimensional arc in mm

All dimensions are in mm.

Any picture shown in this brochure is indicative only



E CRYSTAL ELEVATORS

Registered office: VISHWAS CROWN, Basement floor, Kankanady Old Rd, Mangalore, Karnataka - 575002 +91 98455 35823 info@crystalelevators.com 😵 www.crystalelevators.com